



Cheran's Electric Dryer Conveyor Curing

TECHNICAL SPECIFICATION

MODEL	CC255	CC310	CC315	CC415
Machine Size (LxBxH)	9'x 3'x 4'	14'x 3.5'x 4'	21' x 3.5' x 4'	21'x 5'x 4'
Power	440 V / 50 Hz / 12 HP	440 V / 50 Hz / 20 HP	440 V / 50 Hz / 32 HP	440 V / 50 Hz / 48 HP
Heater	9 KW/ 20.5 Amps	15 KW / 34.5 Amps	24 KW / 54.5 Amps	36 KW / 82 Amps
Working Area	75x150cm (2.5' x 5')	90x300cm (3' x 10')	90 x 450 cm (3' x 15')	120x450cm (4' x 15')
Temperature	200°C	200°C	200 °C	200°C
Operating Speed	33F/min	33F/min	33F/min	33F/min
Conveyor Drive	DC Motor with 180 V DC Drive	DC Motor with 180 V DC Drive	DC Motor with 180 V DC Drive	DC Motor with 180 V DC Drive
Blower	230V AC/ 30W	230V AC/ 30W	230V AC/30 W	230V AC/ 30W

FEATURES

- Radiant quartz heater for immediate heating and cooling
- Variable speed control system
- Suitable for discharge drying
- Manual operation of conveyor also possible during power cuts
- Individual chamber can be controlled-optional
- Suitable for garments / cloth, bags, non oven bags, jute bags and cotton bags
- Suction blower is provided to suck the odour and smoke
- SSR optional
- Extension Conveyor also available

