



## Cheran's Digital Heat Transfer / Fusing Machine

### FEATURES

- Micro control based digital temperature and timer control
- Automatic double stroke operation and production monitoring
- Can be used for collar, cuff, leather, shoes and upholstery items
- Die cast heater bed with Teflon coating is used for longer life

### TECHNICAL SPECIFICATION

Model	CF 2002	CF 2030	CF 2224	CF 2430
Platen Size	40x50cm (16" x 20")	50x75cm (20" x 30")	55 x60cm (22" x 24")	60x75cm (24" x 30")
Power	230V, 50 HZ, 3.5HP	230V, 50 HZ, 5 HP	230V, 50 HZ, 5 HP	230V, 50 HZ, 5.5 HP
Heater	2.5 KW / 11 Amps	3.5 KW / 15 Amps	3.5 KW / 15 Amps	4 KW / 17.5 Amps
Temperature	220°C	220°C	220°C	220°C
Timer	0 to 99 Sec	0 to 99 Sec	0 to 99 Sec	0 to 99 Sec
Air Pressure	0 - 8 Bar	0 - 8 Bar	0 - 8 Bar	0 - 8 Bar
Air Consumption	0.4 cfm at 8 Bar	0.6 cfm at 8 Bar	0.6 cfm at 8 Bar	0.6 cfm at 8 Bar / Min

