## Fasson® Fassheet Plus NG/Removable R-5105/ Kraft n.i

Product Identification Number: BLA 4570

Facestock:

Fasson® Fassheet NG: A smooth, white, semi gloss all purpose finished sheet with the

characteristics necessary for die cutting and stripping

**Basis Weight:** 80 gsm  $\pm$  10% (ISO 536) **Caliper:** 0.068mm  $\pm$  10% (ISO 534)

Adhesive:

Removable R-5105: An aggressive removable adhesive, with excellent tack and good

adhesion on a wide variety of substrates including plastics. Featuring

superior removability from most substrates.

Minimum Application Temperature : 0° C

(The minimum temperature at which the label can be applied and will adhere)

**Service Temperature Range :**  $-40^{\circ}$  C to  $+70^{\circ}$  C

(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)

Liner:

**Fasson® Kraft:** A super-calendered kraft liner with excellent strength properties. ( Non

imprint liner)

**Basis Weight:** 65 gsm ± 10% (ISO 536) **Caliper:** 0.063mm + 10% (ISO 534)

**Application and Use:** Typical applications include general purpose removable labels.

**Conversion:** The product is engineered to provide excellent printability

with solid colours in addition to good lay flat characteristics desired for optimum performance in sheet applications. The product is suited to single and/or multicolour line printing by Offset or Screen. A higher gloss finish can be achieved by additional varnishing or over laminating. Exposure of sheets to high humidity conditions should

be minimized.

**Shelf Life:** Two years when stored at 22° C / 50% RH.

As with all self-adhesive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

Version 25100012i

Avery Dennison (India) Pvt. Ltd. Narsinghpur Industrial Area Six Kilometer stone Delhi-Jaipur Highway Gurgaon-122001,Haryana Tel +91-124—2215581/582/583

Fax +91-124-2215591/592

