



BMB1450

Fasson[®]FasSheet Art Plus Hi-Bond/ Permanent

A Smooth white, machine coated semigloss paper exhibiting good printability.

Applications







Salient Features

- > Robust construction and packaging, suitable for ready to print sheet application.
- > Low adhesive build-up on presses.
- **▶** High adhesion on wide range of substrates.
- Consistent quality enabling high converting and printing efficiency.
- > Defined Service guidelines.

Facestock

A white, machine coated semigloss paper, exhibiting excellent printing

characteristics.

Basis Weight: $72 \text{ gsm} \pm 10\%$ ISO 536 Caliper: $58 \mu\text{m} \pm 10\%$ ISO 534

Adhesive

A permanent Hi-Bond rubber based adhesive featuring high initial tack and ultimate bond strength. The adhesive is engineered specially for substrates with rough texture.

Line

A super calendered kraft liner featuring excellent strength characteristics.

Basis Weight: $65 \text{ gsm} \pm 10\%$ ISO 536 Caliper: $60 \text{ } \mu\text{m} \pm 10\%$ ISO 534

Laminate

Total Construction Caliper 128 μ m $\pm 10\%$

Performance data

Min. Appl. Temp. 5°C

Service Temp. -20°C to 70°C

Applications and use

Product is engineered for good adhesion on difficult to adhesion surfaces like PE, HDPE, PP & Corrugated paper. Applications include labels for Cosmetics, Toiletries, Household containers and other Health and Beauty Aids products, Promotional Labeling as well as shipper labels for corrugated boxes. Hi Bond adhesive is in compliance with FDA 175.105 recommendations for indirect food contact.

Conversion/printing

Fasson® Fassheet Art Hi-Bond product has good lay flat characteristics desired for optimum performance in sheet applications. The product is suited to single and/or multicolour line printing by Offset or Screen. A higher gloss finish can be achieved by additional varnishing or over laminating. Exposure of sheets to high humidity conditions should be minimized.


Shelf life

Two years when stored at 22°C at 50% RH.

BMB1450

Fasson®

FasSheet Art Plus Hi-Bond/ Permanent



Fassheet Art

Hi Bond Adhesive

CK65Wh IMP

Avery Dennison India Pvt. Ltd.

Gurgaon: Pune:

Narsinghpur Industrial Area, Delhi – Jaipur Highway, District Gurgaon, Haryana. India. 122001

Tel: +91 124 4351200

G-5, MIDC Ranjangaon Industrial Area, Taluka - Shirur ,

District – Pune, Maharashtra

India. 412220

Tel: +91 2138 664200

Bengaluru: Plot No. 18 & 23, Peenya Industrial Area,

Phase-I, Yeshwantpur Hobli, District – Bengaluru, Karnataka India. 560058

Tel: +91 80 43316888

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do no constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsable for claims beyond the replacement value of the defective product or in any way

liable or responsable for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTIBILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERNATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.