

Fasson® Fassheet Litho/Permanent

Product Identification Number: BM17123

Facestock:

Fasson® Litho : A bright white, flexible, wood-free paper with good printability and smudge resistance.

Basis Weight : 70 gsm \pm 10% (ISO 536)

Caliper: 0.085 mm \pm 10% (ISO 534)

Adhesive:

Fasson® : Permanent A general-purpose permanent rubber based adhesive featuring high initial tack and ultimate bond strength.

Minimum Application Temperature: 5° C
(The minimum temperature at which the label can be applied and will adhere)

Service Temperature Range: - 20° C to + 70° C
(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)

Liner:

Fasson® Kraft: A super-calendered kraft liner with excellent strength properties.

Basis Weight: 65 gsm \pm 10% (ISO 536)

Caliper: 0.060mm \pm 10% (ISO 534)

Total Construction Caliper : 0.145 mm \pm 10%

Application and Use : The product is specially designed for A-4 size sheet applications demanding good initial tack and high ultimate adhesion onto a wide variety of substrates.

Conversion : **Fasson® Fassheet Litho** product is specially suited to single and/or multi-colour line printing by Letterpress, Offset, and Flexo, for price-marking applications, where flood-coating may be desired. Excellent conversion characteristics in rotary and flatbed presses.

Shelf Life : Two years when stored at 22° C / 50% RH.

As with all self-adhesive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

Version 33600014

Avery Dennison (India) Pvt. Ltd.
Narsinghpur Industrial Area
Six Kilometer stone
Delhi-Jaipur Highway
Gurgaon-122001, Haryana
Tel +91-124—2215581/582/583
Fax +91-124-2215591/592

